

Encoder Interface Box EUI-01/02



An encoder to USB converter EUI-01/02 translates encoder position to industry standards USB 2.0 format that can be read by computer.

- ◆ 32 bit real time up/down counter.
- ◆ Count range from 0 to 4294967295.
- ◆ Very high speed. measures up to 12.5 Mhz input frequency.
- ◆ Two encoders can be interfaced with EUI-02
- ◆ Following facility available through USB input.
 - Reset
 - Preset
 - Reset on index pulse
 - Preset on index pulse
- ◆ USB 2.0 compliant
- ◆ No need of external power supply. Connects directly to a computer's USB port.
- ◆ Quadrature X4 differential 5V TTL input.
- ◆ Easy to use with window's driver and demo software in VB.net.
- ◆ Ideal for
 - Data acquisition
 - PC based control applications.

Note : Due to continues R&D activities at our end, Specifications are subject to change without prior notice.

Marketed by :



HO & Factory : B/24, M.I.D.C., Industrial Estate, Satara : 415 004 Maharashtra (INDIA)

sales@innovatedro.com www.innovatedro.com

+91-2162-245 966
246 509

+91-2162-248 012

Sales Office : B-5, Golden Orchid, Sector No 11, Plot No. 136, New Pradhikaran-Chikhali Road, Bhosari, Pune : 411 019, INDIA +91-20-6510 2543, 6510 2593